

Harmony™ Fountain

We hope you will find these instructions helpful in setting up your product.

If you have any issues with this item, DO NOT return the unit to place of purchase.

Please visit our web site www.angelodecor.com for assistance and warranty information.

AD92286



Arrange all pieces in your workspace.



Pass the power cord down the cord pipe in the large bowl.



Carefully rest the bowl on its side and pass the pump cord down the pedestal.



Align the pump cord with the groove at the base of the pedestal.



Carefully lower the large bowl on to the pedestal. Align the grooves, then twist and lock it to the pedestal.



The pump is preset to full strength. If splash is a concern, adjust as needed.



Install the cord pipe cover over the cord pipe. Attach the tubing to the pump.



Set the pump housing / riser into place, align the grooves then twist and lock it to the bowl.



Pass the tubing through the middle then lower and lock the small bowl to the riser.



Connect the tubing to the top.



Align the top then lower and lock it to the small bowl.



Check to ensure the tubing is still attached to the pump. Install the pump access door.



The included 'shims' can be used to level the fountain if needed.

The final assembly should look like this



Fill with clean water and plug into a grounded GFCI outlet.

The pump must be fully submersed at all times to avoid pump burnout.

Product must be properly stored for winter.

Fontaine Harmony™

AD92286



Nous espérons que vous trouverez ces instructions utiles en assemblant votre produit.

Si vous avez n'importe quelles issues avec cet article, ne renvoyez pas l'unité à l'endroit de l'achat.

Veuillez visiter notre site Web www.angelodecor.com pour l'information d'aide et de garantie.



Arrangez tous les morceaux dans votre zone de travail.



Passez le cordon de secteur en bas de la pipe de corde dans la grande cuvette.



Reposez soigneusement la cuvette de son côté et passez la corde de pompe en bas du piédestal.



Alignez la corde de pompe avec la cannelure à la base du piédestal.



Abaissez soigneusement la grande cuvette dessus au piédestal. Alignez les cannelures, puis tordez-et fermez- à clefles au piédestal.



La pompe est pré-réglée à la pleine force. Si l'éclaboussure est un souci, ajustez comme nécessaire.



Installez la couverture de pipe de corde au-dessus de la pipe de corde. Attachez la tuyauterie à la pompe.




Placez le logement de pompe / canalisation verticale dans l'endroit, alignez les cannelures puis tordez-et fermez- à clefles dans la cuvette.



Passez la tuyauterie par le milieu puis plus bas et fermez à clef la petite cuvette à la canalisation verticale.



Reliez la tuyauterie au dessus.



Alignez le dessus puis plus bas et fermez- à clef dans la petite cuvette.



Vérifiez pour s'assurer que la tuyauterie est encore fixée à la pompe. Installez la porte d'accès de pompe.



Les cales incluses peuvent être employées pour niveler la fontaine si nécessaires.

L'assemblée finale devrait ressembler à ceci



Remplissez d'eau propre et branchez dans une prise de mise à terre DDFT.

La pompe doit être entièrement submersed à tout moment pour éviter d'endommager la pompe.

Le produit doit être entreposé adéquatement durant l'hiver.